

maximal erreichbare längen der KLOTZ RamCAT kabel in abhängigkeit zum übertragungsprotokoll

RamCAT DrumLink	kabeltyp	RamCAT kabel meterware
RC5EED / RC5EEW / RC5RRW / RC-EEW	CAT5e - S/UTP - AWG 26/19	RC5-LB1S / RC5-LB1V / RC5-LB5V
RCBEED / RCBEEW / RCBRRW / RCB2EEW / RCB2RRW / RCMCCW	CAT5e - SF/UTP - AWG 24/1	RC5-SB1X / RC5-SB2 / RC5-SB2A
RC6EEW / RC6PPW	CAT6 - SF/UTP - AWG 26/19	RC6-LB1RJ
RC6AEEW / RC6ARRW	CAT6a - SF/UTP - AWG 23/1	RC6A-SB1X

distanz in metern [m]	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160
AES67 - Ravenna LAWO / DirectOut / Neumann	75 m																
	120 m																
	60 m																
	120 m																
Dante™ getestet von YAMAHA UK	75 m																
	120 m																
	60 m																
	120 m																
AES50 SuperMAC/HyperMAC Midas / Behringer	50 m																
	100 m																
	60 m																
	100 m																
AVB AVID / Meyer Sound / Adamson	50 m																
	100 m																
	60 m																
	100 m																
MADI over Ethernet Soundcraft / Digico	50 m																
	120 m																
	60 m																
	120 m																
GigaACE getestet von Allen&Heath	75 m																
	100 m																
	60 m																
	100 m																
Ethersound™ getestet von Digigram	75 m																
	120 m																
	60 m																
	120 m																
RockNet RIEDEL	50 m																
	150 m																
	50 m																
	150 m																
1000Base-T (Gbit Ethernet) NDI / BLU link	60m																
	100 m																
	60m																
	100 m																
10GBase-T (10Gbit Ethernet) NDI / BLU link	not supported																
	not supported																
	60 m																
	100 m																
distanz in metern [m]	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160